

EMERALD ESTATES UNIT FOUR

A PORTION OF C.D. STEWART SURVEY NO. 320 EL PASO COUNTY, TEXAS. CONTAINING 29.348 ACRES ±

DESCRIPTION

DESCRIPTION OF A 29.348 ACRE TRACT OF LAND, SITUATED IN THE C.D. STEWART SURVEY NO. 320 OF EL PASO COUNTY, TEXAS SAID 29.348 ACRE TRACT BEING DESCRIBED BY METES AND BOUNDS AS FOLLOWS:

COMMENCING at a point at the southeast corner of said C.D. Stewart Survey No. 320, being also the southwest corner of the W.J. Rand Survey No. 325, being also the northwest corner of the C.D. Stewart Survey No. 321 and being northeast corner of C.D.

THENCE, N 49°26'38" W, for a distance of 1791.93 feet to a 5/8 inch iron rod with cap stamped "ZWA" set at southeast of the herein described tract and the POINT OF BEGINNING,

THENCE, N 53°08'40" W, for a distance of 105.97 feet to a 5/8 inch iron rod set with cap stamped "ZWA" THENCE, N 25°44'07" E, for a distance of 16.69 feet to a 5/8 inch iron rod set with cap stamped "ZWA";

THENCE, N 24°36'55" E, for a distance of 253.11 feet to a 5/8 inch iron rod set with cap stamped "ZWA" set at the beginning o

THENCE, along said compound curve to the left, having an arc length of 32.89 feet, a radius of 20.00 feet, a delta angle of 94°12'20", with a chord bearing of N 28°13'26" W, for a chord distance of 29.31 feet to a 5/8 inch iron rod set with cap

THENCE, N 75°14'51" W, for a distance of 38.37 feet to a 5/8 inch iron rod with cap stamped "ZWA" set at the beginning a

THENCE along said curve to the left, having an arc length of 307.78 feet, a radius of 1100.00 feet, a delta angle of 16°0152", with a chord bearing of N 83°15'56" W, for a chord distance of 306.77 feet to a 5/8 inch iron rod set with cap samped "ZWA".

THENCE, N 01°16'52" W, for a distance of 60.00 feet to a 5/8 inch iron rod set with of

THENCE, N 01°52'36" E, for a distance of 158.50 feet to a 5/8 inch iron rod set with cap stamped "ZWA"

THENCE, N 07°15'40" W, for a distance of 123.25 feet to a 5/8 inch iron rod set with cap stamped "ZWA"

THENCE, N 44°40'52" W. for a distance of 268.00 feet to a 5/8 inch iron rod set with cap stamped "ZWA"

THENCE, N 45°19'08" E, for a distance of 100.00 feet to a 5/8 inch iron rod set with cap stamped "ZWA" at the beginning of a

THENCE, along said curve to the left, having an arc length of 29.85 feet, a radius of 19.00 feet, a delta angle of 90°00′00″, with a chord bearing of N 00°19′08″ E, for a chord distance of 26.87 feet to a 5/8 inch iron rod set with can stamped "ZWA":

THENCE, N 45°19'08" E. for a distance of 54.00 feet to a 5/8 inch iron rod set with cap stamped "ZWA" at the beginning of a

THENCE, along said curve to the left, having an arc length of 29.85 feet, a radius of 19.00 feet, a delta angle of 90°00'00", with a chord bearing of \$ 89°40"52" E, for a chord distance of 26.87 feet to a 5/8 inch iron rod set with cap stamped "ZWA";

THENCE, N 45°19'08" E, for a distance of 100.00 feet to a 5/8 inch iron rod set with cap stamped "ZWA":

THENCE, N 25°50'35" W, for a distance of 273.43 feet to a 5/8 inch iron rod set with cap:

THENCE, N 76°19'01" E, for a distance of 156.32 feet to a 5/8 inch iron rod set with cap stamped "ZWA"

THENCE, S 81°57'55" E, for a distance of 74.56 feet to a 5/8 inch iron rod set with cap stamped "ZWA"

THENCE, N 22°36'48" E, for a distance of 13.97 feet to a 5/8 inch iron rod set with cap stamped "ZWA";

THENCE, N 00°14'34" E, for a distance of 121.68 feet to a 5/8 inch iron rod set with cap stamped "ZWA";

THENCE, N 00°14'16" E, for a distance of 64.00 feet to a 5/8 inch iron rod set with cap stamped "ZWA" at the beginning of a

THENCE, along said curve to the right, having an arc length of 72.44 feet, a radius of 1485.21 feet, a delta angle of 02°47'43", with a chord bearing of S 88°22'57" E, for a chord distance of 72.43 feet to a 5/8 inch iron rod set with cap samped "2WA".

THENCE, S 86°58'55" E, for a distance of 42.08 feet to a 5/8 inch iron rod set with cap stamped "ZWA":

THENCE, S 03°00'59" W, for a distance of 64.00 feet to a 5/8 inch iron rod set with cap stamped "ZWA";

THENCE, S 86°59'01" E, for a distance of 538.43 feet to a 5/8 inch iron rod set with cap stamped "ZWA" for t

THENCE, S 02°27'34" W, for a distance of 1568.06 feet to a 5/8 inch iron rod set with cap stamped "ZWA".

THENCE N 42°42°12" W. for a distance of 113 60 feet to a 5/8 inch iron rad set with can stamped "7WA" THENCE, S 39°22'44" W, for a distance of 107.08 feet to a 5/8 inch iron rod set with can stamped "ZWA":

THENCE, S 36°51'20" W, for a distance of 103.79 feet to the POINT OF BEGINNING, and containing me



Professional Land Surveyors Job # 2079-01

THIS PLAT REPRESENTS A SURVEY MADE ON THE GROUND UNDER MY SUPERVISION AND IS IN COMPLIANCE WITH THE CURRENT TEXAS BOARD OF PROFESSIONAL LAND SURVEYIN

G. RENE ZAMORA, R.P.L.S. TX. NO. 5682

SURVEYOR'S DEDICATION

DATE OF PREPARATION: SEPTEMBER, 2019

Emerald Estates	Price	Lot sf	Hm sf	Lot	Block	Front	Back	Left	Right
13480 Rain Court	\$88,000.00	11,767		4	8	75	105	124	145
323 Emerald Tree Lane	\$83,000.00	11,543		24	8	61	94	139	171
300 Emerald Rise Drive	\$79,500.00	11,004		26	8	69	102	146	124
324 Emerald Rise Drive	\$62,500.00	8,497		32	8	60	81	119	126
320 Emerald Night Drive	\$94,500.00	14,995		18	9	46	138	115	110
325 Emerald Night Drive	\$95,000.00	14,514		19	9	62	173	123	141
329 Emerald Night Drive	\$81,500.00	11,816		20	9	84	79	141	134
333 Emerald Night Drive	\$74,000.00	8,865		21	9	70	72	134	118
341 Emerald Night Drive	\$74,000.00	8,260		23	9	70	70	118	118
345 Emerald Night Drive	\$74,000.00	8,646		24	9	74	74	118	118
321 Emerald Rise Drive	\$80,000.00	9,415		11	10	96	53	118	130
325 Emerald Rise Dirve	\$69,000.00	9,090		12	10	67	67	130	130